



Specifications Ledvance LED Panel  
Linear Pendant IndiviLED 69W 8150lm  
- 930 Warm White | 150x13cm - UGR  
<19 - Best Colour Rendering - Dali  
Dimmable - Motion And Light Sensor

[View Product](#)

General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 251581                                  |
| EAN                      | 4099854249792                           |
| Manufacturer Code        | 4099854249792                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | LN INV DI 1500 P 69W 930 DAVR SNWT LEDV |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 100000                                  |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 1x58               |
| Wattage                     | 69W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 930 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 8150lm             |

|                          |                    |
|--------------------------|--------------------|
| Luminous Efficacy (lm/W) | 118                |
| IP-rating                | IP20               |
| Impact Protection (IK)   | IK06 - 1 joule     |
| Fixture Connection       | Screwless terminal |
| Power factor             | >0.90              |
| Product Type Category    | LED Panel          |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Suspendu                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 150x13cm |
| Length (mm)    | 1475     |
| Width (mm)     | 125      |
| Height (mm)    | 43       |

## Sensor Information

## Why Any-lamp?

Type of sensor

Light Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process